



DOVER FLEXO ELECTRONICS, INC.  
*TENSION CONTROL AND INDICATION EQUIPMENT*

**FOR IMMEDIATE RELEASE**

Contact: Mark Breen +1-603-332-6150; mbreen@dfe.com

**EasyView™ Tension Indicators**  
with *Quik-Cal™* Push-button Zero and Calibrate



(ROCHESTER, NH, USA—October 22, 2009) Tension measurement and controls manufacturer Dover Flexo Electronics, Inc. (DFE) has launched the **EasyView™** line of tension indicators. **EasyView™** is a compact, low-cost general-purpose web tension amplifier and display for printers, converters and web process manufacturers.

The **EasyView** indicator is powered by 24 Volts DC and amplifies a web tension signal from tension transducers installed in a machine's web path. It displays an accurate tension reading on an analog or digital meter while supplying an isolated 0-to-10 VDC tension signal output to a PLC, drive, or controller.

**Quik-Cal™** is a labor-saving technology. During setup, the operator pushes a ZERO button and a CALIBRATE button for one second each to set the Zero and Span settings, rather than having to turn potentiometers. Because the zero and calibration settings are stored digitally, the output is stable and drift-free over time and temperature variations.

Units are available with an analog meter display or optional digital display, as pictured. Mounting choices are either the full enclosure (E) version for mounting on a machine frame or the open panel mount (P) version for installing into a cutout on and OEM operator panel or cabinet.

EasyView's integrated electrical isolation for output, ease-of-use, and competitive price combine to deliver compelling value for tension monitoring or control applications.

Ask for the **EasyView Indicator** data sheet from DFE or download it at [http://www.dfe.com/products/ind\\_easyview.html](http://www.dfe.com/products/ind_easyview.html).

**www.dfe.com**

217 Pickering Road Rochester NH 03867 USA  
603-332-6150 Fax 603-332-3758 info@dfe.com